



ENLC125-3

Standby power : 125KVA/99KW

Prime power : 112.5KVA/90KW

Standard features

- Engine: CUMMINS , 6BT5.9-G2
- Charge alternator : 24V
- Governor : Electrical
- Generator : LEROY SOMER , LSA44.2 VS3
- Single bearing alternator IP 23
- Insulation class H/H
- Radiator 50°C max with coolant cap
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker
- 24V battery and cable
- Industrial muffler
- User's manual

	Open Type Overall size (L*W*H) 2170mm×880mm×1415mm Weight: 1219kg
	Silent Type Overall size (L*W*H) 2850mm×1100mm×1400mm Weight: 1704kg

Generator Ratings

3-PH, 60Hz@1800RPM, 480/277V (Also Can Be Made According To Customers' Special Requirements)

Voltage	Hz	Phase	Power factor	Standby AMP	Standby rating (KVA/KW)	Primerating (KVA/KW)
480/277	60	3	0.8	149	125/99	112.5/90

Engine data

Manufacturer/Model	CUMMINS 6BT5.9-G2 4-cycle
Cylinder /Arrangement	6/ L
Displacement	5.9 L
Bore and Stroke	102 mm×120 mm
Compression ratio	17.3 : 1
Rated RPM	1800RPM
Max. stand by power at rated RPM	110 KW
Frequency regulation , steady state	≤ 1%
Governor : type	Electrical

Exhaust System

Exhaust gas flow	18.5m ³ /min
Exhaust temperature	565℃
Max back pressure	10KPa

Fuel System

Fuel consumption100% (of the Prime Power)	214 g/Kw.h
---	------------

Oil System

Total oil capacity w/filters	16.4L
------------------------------	-------

Air intake

Engine air flow	108 L/s
-----------------	---------

Coolant System

Radiator & engine capacity	29.0 L
Max water temperature	104℃
Thermostat	82-95℃

Generator Data

Optional: STAMFORD, MARATHON, MECALETE, SMF.

Alternator Model	LSA44.2 VS3 (LEROY SOMER) Please Refer To The“ Genset Main Technical Data”
Phase/Connect	3-phase 4-wire ,Y type connection
Excitation Model	Self-excite,automatic voltage regulation,Insulation:H,Bruhless,Enclosure:IP21—IP23
Power Factor	0.8
The regulating rate of instantaneous voltage:	-15%~ +20%
The time of steady voltage:	≤1.5sec
The waving rate of voltage:	≤1.0%
The regulating rate of steady frequency:	≤5%
regulating rate of instantaneous frequency:	≤±10%
The time of steady frequency:	3sec
The waving rate of frequency:	≤1%

Control panel**Optional:** DSE3110, AMF20, HGM6110, HGM6120.....

The DSE6010 is an Auto Start Control Module and the DSE6020 is an Auto Mains (Utility) Failure Control Module for single gen-set applications .

Both modules have been designed to work with electronic and non electronic engines providing advanced engine monitoring and protection features .