



ENLD75-3

Standby power : 75KVA/60KW

Prime power : 70KVA/56KW

Standard features

- Engine: DEUTZ(DALIAN) , BF4M2012
- Charge alternator : 24V
- Governor : Mechanical
- Generator : LEROY SOMER , LSA42.3 L9
- Single bearing alternator IP 23
- Insulation class H/H
- Radiator 50°C max with coolant cap
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker
- 24V battery and cable
- Industrial muffler
- User's manual

	Open Type Overall size (L*W*H) 2000mm×750mm×1300mm Weight: 1050kg
	Silent Type Overall size (L*W*H) 2440mm×1060mm×1680mm Weight: 1550kg

Generator Ratings

3-PH, 60Hz@1500RPM, 480/277V (Also Can Be Made According To Customers' Special Requirements)

Voltage	Hz	Phase	Power factor	Standby AMP	Standby rating (KVA/KW)	Primerating (KVA/KW)
480/277	60	3	0.8	90	75/60	70/56

Engine data

Manufacturer/Model	DEUTZ(DALIAN) , BF4M2012 4-cycle
Cylinder /Arrangement	4 / L
Displacement	4.04L
Bore and Stroke	101mm×126 mm
Compression ratio	18.4 : 1
Rated RPM	1800 RPM
Max. stand by power at rated RPM	70 KW
Frequency regulation , steady state	≤ 1%
Governor : type	Mechanical Governo

Exhaust System

Exhaust gas flow	14.5m ³ /min
Exhaust temperature	600°C
Max back pressure	2.5kPa

Fuel System

Fuel consumption100% (of the Prime Power)	221 g/KWh
---	-----------

Oil System

Total oil capacity w/filters	8.5L
------------------------------	------

Air intake

Engine air flow	108m ³ /min
-----------------	------------------------

Coolant System

Radiator & engine capacity	15.9L
Max water temperature	110°C
Thermostat	83-98°C

Generator Data

Optional: STAMFORD, MARATHON, MECALETE, SMF.

Alternator Model	LSA42.3 L9 (LEROY SOMER) Please Refer To The“ Genset Main Technical Data”
Phase/Connect	3-phase 4-wire ,Y type connection
Excitation Model	Self-excite,automatic voltage regulation,Insulation:H,Bruhless,Enclosure:IP21—IP23
Power Factor	0.8
The regulating rate of instantaneous voltage:	-15%~ +20%
The time of steady voltage:	≤1.5sec
The waving rate of voltage:	≤1.0%
The regulating rate of steady frequency:	≤5%
regulating rate of instantaneous frequency:	≤±10%
The time of steady frequency:	3sec
The waving rate of frequency:	≤1%

Control panel

Optional: DSE3110, AMF20 , HGM6110 , HGM6120.....



The DSE6010 is an Auto Start Control Module and the DSE6020 is an Auto Mains (Utility) Failure Control Module for single gen-set applications .

Both modules have been designed to work with electronic and non electronic engines providing advanced engine monitoring and protection features .