



ENLC430-3

Standby power : 430KVA/345KW

Prime power : 394KVA/315KW

Standard features

- Engine: CUMMINS , NTA855-G3
- Charge alternator : 24V
- Governor : Electrical
- Generator : LEROY SOMER , LSA46.2 L9
- Single bearing alternator IP 23
- Insulation class H/H
- Radiator 50°C max with coolant cap
- Skid and vibration isolators
- Dry type air filter
- Main line circuit breaker
- 24V battery and cable
- Industrial muffler
- User's manual

	<p>Open Type</p> <p>Overall size (L*W*H) 3050mm×1110mm×1920mm</p> <p>Weight: 2742kg</p>
	<p>Silent Type</p> <p>Overall size (L*W*H) 3900mm×1400mm×1820mm</p> <p>Weight: 3666kg</p>

Generator Ratings

3-PH, 60Hz@1800RPM, 480/277V (Also Can Be Made According To Customers' Special Requirements)

Voltage	Hz	Phase	Power factor	Standby AMP	Standby rating (KVA/KW)	Primerating (KVA/KW)
480/277	60	3	0.8	490	430/345	394/315

Engine data

Manufacturer/Model	CUMMINS NTA855-G3 4-cycle
Cylinder /Arrangement	6/ L
Displacement	14.0L
Bore and Stroke	140mm×152mm
Compression ratio	14.0: 1
Rated RPM	1800 RPM
Max. stand by power at rated RPM	399KW
Frequency regulation , steady state	≤ 1%
Governor : type	Electrical

Exhaust System

Exhaust gas flow	1213L/s
Exhaust temperature	482℃
Max back pressure	10KPa

Fuel System

Fuel consumption100% (of the Prime Power)	82.1L/h
---	---------

Oil System

Total oil capacity w/filters	38.6L
------------------------------	-------

Air intake

Engine air flow	463L/s
-----------------	--------

Coolant System

Radiator & engine capacity	85 L
Max water temperature	104℃
Thermostat	82-94℃

Generator Data

Optional: STAMFORD, MARATHON, MECALETE, SMF.

Alternator Model	LSA46.2 L9 (LEROY SOMER) Please Refer To The“ Genset Main Technical Data”
Phase/Connect	3-phase 4-wire ,Y type connection
Excitation Model	Self-excite,automatic voltage regulation,Insulation:H,Bruhless,Enclosure:IP21—IP23
Power Factor	0.8
The regulating rate of instantaneous voltage:	-15%~ +20%
The time of steady voltage:	≤1.5sec
The waving rate of voltage:	≤1.0%
The regulating rate of steady frequency:	≤5%
regulating rate of instantaneous frequency:	≤±10%
The time of steady frequency:	3sec
The waving rate of frequency:	≤1%

Control panel**Optional:** DSE3110, AMF20, HGM6110, HGM6120.....

The DSE6010 is an Auto Start Control Module and the DSE6020 is an Auto Mains (Utility) Failure Control Module for single gen-set applications .

Both modules have been designed to work with electronic and non electronic engines providing advanced engine monitoring and protection features .